

THE SURFACE FINISHING EQUIPMENT GROUP

SALES – SERVICE - HIRE
TRAINING – INSTALLATION

NORTH EAST BRANCH

**Hogg Blasting
& Finishing Equipment Ltd**
Washington. UK. NE37 1PR

Tel. 0191 415 3030
info@hoggblasting.com

NORTH WEST BRANCH

**Abraclean Ltd and
Jedtec Finishing Equipment**
Stockport. UK. SK5 7PP

Tel: 0161 480 8087
sales@abraclean.co.uk

- Shot Blasting Equipment
- Paint Spraying Equipment
- Powder Coating Equipment
- Fixed Extraction Booths
- Mobile Dust Extraction
- Personal Protection Equipment
- Shot Blasting Abrasives
- Spares and Consumables
- Plural Component Systems

Ercon Finishing Systems
Willenhall. UK. WV13 2JW

Tel. 01902 601 312
sales@erconfinishing.com

- Complete Finishing Plants
- Design engineers and CAD
- Industrial Ovens
- Conveyors
- Pre-treatment systems
- Electroplating Systems



Surface Finishing
Equipment Group

AIRVISOR 2 AIR FED MASK



Airvisor 2 with Full Face Visor, and Waistbelt with Filter/Regulator



Alternative Half
Mask
version shown above

The selection and use of the correct Personal Protective Equipment is essential to effectively protect users from risk by creating a barrier against workplace hazards.

The Airvisor 2 provides a practical solution for operator respiratory protection in paint shop, powder coating, or industrial spraying environments where a high level of protection is required from a wide variety of paints including isocyanates, dusts, powders.

FEATURES :

- Lightweight Acetate Chemical Resistant Full Face Visor or optional Half Mask Visor.
- Complies to Respiratory Standards EN14594:2005
- Waistbelt with Carbon Filter and Tamper-proof Safety Regulator.
- Low Flow warning device / whistle — validates operated safety.
- Diffusor—provides optimum delivery of airflow inside the headpiece.
- Tear-Off Screens can be fitted and peeled off if contaminated with overspray.
- Nominal Protection Factor Class 2 - 100 / Assigned Protection Factor 40.
- 1100g weight

REQUIREMENTS:

- Needs a suitable compressed air supply of breathable quality in accordance with EN12021 and of flow rate above 260 litres / minute at 6.0 bar.
- Needs a Rectus 25 Series Quick Release airline coupling body
This can be supplied as an addition if required.

Notes :

This product only provides correct performance when used in accordance with manufacturer's instructions